

MANUFACTURE STANDARD, MANUFACTURE RELIANCE

RT-**7600***Auto Hematology Analyzer*

Features

- 20 parameters+3 histograms
- 3-part differentiation of WBC
- 2 counting modes: whole blood and prediluted
- 60 samples per hour
- 10.4" TFT colorful LCD with touch screen
- Built-in thermal printer, optional external printer
- External AC adapter avoids electronic nosies, enhancing accuracy
- Up to 50000 sample results (including histograms) can be stored
- Multi-language software available on request
- Original factory's blood control and calibrator



RT-7600


Auto Hematology Analyzer



Auto Calibration Setting



L-J QC Setting



Technical Specifications

Parameters	WBC, LYM#, MID#, GRA#, LYM%, MID%, GRA%, RBC, HGB, MCHC, MCH, MCV, RDW-CV, RDW-SD, HCT, PLT, MPV, PDW, PCT, P-LCR and Histograms for WBC, RBC and PLT
Principle	Electrical resistance for counting WBC, RBC and PLT
Sample Volume	Prediluted:20µL; Whole Blood:9.8µL
Throughput	60 samples per hour
Display	10.4" TFT color LCD with touch screen
Alarms	Error messages
Input/Output	RS-232, USB, LAN, keyboard and mouse interface
Printout	Thermal printer, 55mm width paper, various printout formats, external printer optional
Operating Environment	Temperature: 15°C~35°C; Humidity: ≤80%
Power Requirement	AC 110V-220V, 50/60Hz
Dimension L×W×H (mm)	436×363×367
Weight	18Kg

Rayto Life and Analytical Sciences Co.,Ltd.

2nd Floor, 5th Building, Software Park, NO.2, Gaoxinzhong
3rd Road, High-tech Industrial Park, Nanshan,
Shenzhen 518057, P.R.China
Tel: +86(755)86168182 Fax: +86(755)86168796
Email: info@rayto.com