



WHAT'S NEW

20 PARAMETERS
+ 3 HISTOGRAMS

2 COUNTING CHANNELS

TOUCH SCREEN &
LARGE LCD COLOUR

LOW REAGENT
CONSUMPTION

Automated Hematology Analyzer

WP-360



Features


- 20 parameters + 3 histograms
- 3-part differentiation of WBC
- 2 Counting mode : whole blood and prediluted
- Throughput : up to 60 samples per hour
- 10.4" TFT colorful LCD with touch screen
- Built-in thermal paper, optional external printer
- External AC adapter avoids electronic noises, enhancing accuracy.
- Up to 50000 sample results (including histograms) can be stored
- Original factory's reagents, blood control and calibrator



get the Guaranteed Satisfaction from us

WP-360

Automated Hematology Analyzer




SampleTest

Auto Calibration Setting



Manual Calibration

L-J QC Setting



Profile

Technical Specifications

Parameters	WBC, LYM#, MID#, GRA#, LY%, MID%, GRA%, RBC, HGB, MCHC, MCH, MCV, RDW-CV, RDW-SD, HCT, PLT, MPV, PDW, PCT, P-LCR and Histograms for WBC, RBC and PLT
Principle	Electrical resistance for counting WBC, RBC and PLT
Sample Volume	Prediluted:20µL; Whole Blood:9.8µL
Throughput	60 samples per hour
Display	10.4" TFT color LCD with touch screen
Alarms	Error messages
Input/Output	RS-232, USB, LAN, keyboard and mouse interface
Printout	Thermal printer, 55mm width paper, various printout formats, external printer optional
Operating Environment	Temperature: 15°C~35°C; Humidity: ≤80%
Power Requirement	AC 110V-220V, 50/60Hz
Dimension L×W×H (mm)	436×363×367
Weight	18Kg

Original Reagents, Controls & Calibrators



get the **Guaranteed Satisfaction** from us